


FORWARD RELAYS



20×10×12

M4

c  us E158859  R50044268

Features

- DIL pitch terminals. High sensitivity.
- Conforms to FCC Part 68 1.5kV surge and dielectric 1000VAC.
- High reliability bifurcated contact.
- Application for telecommunication equipment, office equipment, security alarm systems, measuring instruments, medical monitoring equipment, audio visual equipment, flight simulator, sensor control.

Ordering Information

M4 12 H W A
1 2 3 4 5

1 Part number: M4
2 Coil rated voltage: DC:3:3V; 5:5V; 6:6V; 9:9V;
12:12V; 24:24V; 48:48V

3 Enclosure: H: Wash tight
4 Contact material: Nil: AgPd; W: AgNi
5 Nominal coil power: Nil:0.15W; A:0.2W

Contact Data

Contact Arrangement	2C(DPDT(B-M)) (Bifurcated Crossbar)		
Contact Material	AgPd(Au plated) AgNi(Au plated)		
Contact Rating (Resistive)	1A/24VDC; 2A/30VDC; 0.5A/120VAC		
Max. Switching Power	60W 125VA	Min. Switching Load: 0.01mA/10mV(Reference Value)	
Max. Switching Voltage	220VDC 250VAC	Max. Switching Current:2A	
Contact Resistance	≤50mΩ	Item 4.12 of IEC 61810-7	
Operational Life	Electrical	1A/24VDC: 5×10^5 (Ag Ni : 1×10^5) 2A/30VDC: 1×10^5 0.5A/120VAC: 2×10^5	Item 4.30 of IEC 61810-7
	Mechanical	1×10^6	Item 4.30 of IEC 61810-7

CAUTION:

Relays previously tested or used above 10mA resistive at 6VDC maximum or peak AC open circuit are not recommended for subsequent use in low level applications.

Coil Parameter

Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pick-up voltage VDC(max) (70% or 66% of rated voltage)	Drop-out voltage VDC(min) (5% or 10% of rated voltage)	Coil power W	Operate time ms	Release time ms
	Rated	Max.						
M4-003	3	7.5	60	2.1	0.15	0.15	Approx. 4.5	Approx. 1.5
M4-005	5	12.5	167	3.5	0.25	0.15		
M4-006	6	15.0	240	4.2	0.3	0.15		
M4-009	9	22.5	540	6.3	0.45	0.15		
M4-012	12	30.0	960	8.4	0.6	0.15		
M4-024	24	52.9	2880	16.8	1.2	0.15		
M4-048	48	84.9	7680	33.6	2.4	0.30	Approx. 4.5	Approx. 1.5
M4-003A	3	6.5	45	2.1	0.3	0.2		
M4-005A	5	10.8	125	3.5	0.5	0.2		
M4-006A	6	13.0	180	4.2	0.6	0.2		
M4-009A	9	19.5	405	6.3	0.9	0.2		
M4-012A	12	26.5	720	8.4	1.2	0.2		
M4-024A	24	52.9	2880	16.8	2.4	0.2		
M4-048A	48	103.9	11520	33.6	4.8	0.2		

- CAUTION:**
- 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
 - 2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.
 - 3.Unless otherwise stated, the rated coil voltage specified in coil parameter table shall be used for all tests and its application to the relay.

Characteristics


Electrostatic Capacitance		
Between Open Contacts	Approx.0.7pF	Item 4.41 of IEC 61810-7
Between Coil & Contacts	Approx.1.0pF	Item 4.41 of IEC 61810-7
Between Contact Poles	Approx.0.9pF	Item 4.41 of IEC 61810-7
Insulation Resistance	1000M Ω min (at 500VDC)	Item 4.11 of IEC 61810-7
Dielectric Strength		
Between Open Contacts Between Coil & Contacts Between Contact Poles	1000VAC 1min 1000VAC 1min 1000VAC 1min	Item 4.9 of IEC 61810-7
Surge Withstand Voltage		
Between Open Contacts Between Coil & Contacts Between Contact Poles	1500V 1500V 1500V	FCC 68
Shock Resistance	Functional:98m/s ² 11ms; Destructive:980 m/s ² 6ms	Item 4.26 of IEC 61810-7
Vibration Resistance	10Hz~55Hz Double amplitude Functional:1.5mm Destructive:5mm	Item 4.28 of IEC 61810-7
Terminals Strength	5N	Item 4.24 of IEC 61810-7
Temperature Range	-40°C~90°C(-40° F~194° F) (-40°C~80°C for 0.3W Coil)	
Mass	Approx. 4.8g	Item 4.7 of IEC 61810-7

Safety Approvals


Safety approval	UL&CUR	TUV
Load	1A/24VDC; 2A/30VDC; 0.5A/120VAC	1A/24VDC; 0.5A/120VAC

Dimensions


mm



Dimensions




Wiring diagram
(Bottom view)



Mounting (Bottom view)

CAUTION: In case of no tolerance shown in outline dimension: outline dimension $\leq 1\text{mm}$, tolerance should be $\pm 0.2\text{mm}$; outline dimension $> 1\text{mm}$ and $\leq 5\text{mm}$, tolerance should be $\pm 0.3\text{mm}$; outline dimension $> 5\text{mm}$, tolerance should be $\pm 0.4\text{mm}$.

FORWARD RELAYS



M4/M1B Series Data

